

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 September 2003 (18.09.2003)


PCT

(10) International Publication Number
WO 03/077527 A1

- (51) International Patent Classification⁷: **H04M 15/00**
- (21) International Application Number: PCT/EP03/01978
- (22) International Filing Date: 26 February 2003 (26.02.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
TO2002A000201 8 March 2002 (08.03.2002) IT
- (71) Applicant (for all designated States except US): **TELECOM ITALIA S.P.A.** [IT/IT]; Piazza degli Affari, 2, I-20123 Milano (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **DE PAOLA, Maurizio** [IT/IT]; Telecom Italia S.p.A., Via G. Reiss Romoli, 274, I-10148 Torino (IT). **PARATA, Dario** [IT/IT];
- (74) Agent: **GIANNESI, Pier, Giovanni**; Pirelli S.p.A., Viale Sarca, 222, I-20126 Milano (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: METHOD FOR DECODING CHARGING DATA RECORDS IN MOBILE TELEPHONE NETWORKS AND THE RELATIVE SYSTEM



(57) Abstract: The invention relates to the decoding of charging data records (CDR) generated in a mobile telephone network. These records consist of files to be decoded that can be described on the basis of a formal description of the ASN.1 type. On the basis of: i) a description of the type of record to be decoded corresponding to at least a first type (GSM) and at least a second type (GPRS) of records to be decoded, and on the basis of ii) said formal description of the type ASN.1 of the records to be decoded, an interpreter of the ASN.1 type (18) self-generates an updated version of decoder (10) of at least a first and at least a second type according to the type of record to be decoded. The files to be decoded are sent to the decoder created in this way, so as to output the decoded CDR records in text format.



WO 03/077527 A1

**Declarations under Rule 4.17:**

- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for the following designations AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VC, VN, YU, ZA, ZM, ZW, ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent

(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG)

- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

**METHOD FOR DECODING CHARGING DATA RECORDS IN MOBILE
TELEPHONE NETWORKS AND THE RELATIVE SYSTEM**

Technical Field

The present invention tackles the problem of decoding
5 the so-called Charging Data Records (normally known by the
acronym CDR) emitted by the nodes of a mobile telephone
network.

Background Art

These charging data records are currently decoded by
10 employing solutions based on software applications, which,
for example, decode GSM network records separately from those
of an associated GPRS network. Specifically, the application
is developed manually starting from the record coding
specifications, and each time there is a modification/new
15 release of the GSM and/or GPRS systems and when new functions
are added, parts of the software must be to some extent
rewritten.

There is consequently a need to provide solutions that
can decode both GSM and GPRS format records, and for
20 solutions that take into account the frequent updating of the
record format after the introduction of new GSM and GPRS
network services/performances, as well as the possibility of
easy extension of the application to new functions such as
UMTS.

25 This objective can be reached, according to this
invention, by using a method that has the features referred
to specifically in the claims that follow. The invention also
refers to the relative system.

Summary of the invention

30 The solution, according to this invention, basically
envisages the automatic generation of the logic that decodes
the records. Whereas known solutions include the rewriting of
the record decoding software whenever variations are

introduced by the MSC manufacturer (Mobile Switching Center) or SGSN/GGSN (Serving GPRS Support Node and Gateway GPRS Support Node), the solution according to the invention simply requires the manufacturer to provide a formal record
5 description of the ASN.1 type (Abstract Syntax Notation One). The solution, according to the invention, then uses this description to directly generate the code that decodes the data record. As a result, the decoder adaptation times can be cut from several weeks to a few days, making it easy to keep
10 right up to date with the mobile network's frequent alterations.

The solution, according to the invention, includes the decoding of GSM records and GPRS records, which means that a single tool can be used on a mixed network employing both
15 technologies. This is particularly advantageous if you consider that the operators of large-scale mobile telephone networks use both technologies in the network, in conditions in which the network update is carried out asynchronously. The solution, according to the invention, proposes to decode
20 the data records for GSM and GPRS functions, but its main features also make it easy and quick to extend the solution to other functions such as UMTS.

Brief Description of Drawings

The invention is hereafter described, by way of a non-
25 limiting example only, with reference to the annexed drawings wherein:

- Figure 1 is a functional block diagram illustrating the general architecture and the input/output/control relationships of a system that operates according to the
30 invention, and
- Figure 2 is a flow diagram illustrating the main stages into which the method is divided according to the invention.

Detailed description of the preferred embodiments

As shown in Figure 1, the illustrated system, referred to with the number 10, has a main element, which is a processing core 12, destined to input a file to be decoded 14, which then outputs a corresponding decoded file 16. The system 12 works on the basis of a decoding logic that is directly self-generated from the formal description ASN.1 contained in a file 20 received from the outside. As already known, the description of the records in ASN.1 (or equivalent, and consequently a description "of the ASN.1 type") constitutes a set of specifications that describe the coding format of the records in ASN.1 Notation or equivalent.

The input or log file 14 contains the records generated by the real network equipment (MSC for GSM records or SGSN/GGSN for GPRS records) in coded hexadecimal format.

The decoding operation is run on the basis of the set of user parameters that characterise the log file, the type of record (SGM/GPRS) and the output format.

In particular, starting from an initial step 100, the first steps in the operating sequence of the system 10 include the reading of the parameters sent to output, which are:

- type of record to be decoded: GSM or GPRS (read by the system in step 102),
- name of the log file to be decoded (step 104),
- decoding format, i.e. the output format of the decoded file (read in step 106); this format may be "long", when the decoding, the length and the contents in hexadecimal are given for each record field, or "short", when only the decoding is given for each record field,
- log file containing the records to be decoded (step 108), and
- formal record description of the ASN.1 type (step 110).

Depending on the record description, an interpreter, such as an ASN.1 interpreter, included in the processing core 12 (see block 18 in Figure 1) creates and runs a series of procedures (collectively referred to as 112), which in terms of a self-generation operation, create an updated version of the GSM decoder (step 114) or GPRS decoder (step 116) according to the type of record read in step 102.

The type of decoder selected (114 or 116) according to the parameter indicating the type of record (step 102) is further parameterised according to the parameters read in steps 104 and 106 (log file name and decoding format).

Once the decoder has been updated and programmed, it inputs (step 118) the file 14 containing the records to be decoded, and then outputs (step 120) the file containing the records decoded in text format. Reference 122 indicates the final step in the procedure.

Naturally, numerous changes can be made to the construction and embodiments of the invention envisaged and illustrated herein, without however departing from the scope of the present invention.

CLAIMS

1. Method for decoding charging data records (CDR) generated in a mobile telephone network, said records consisting of files to be decoded that can be described on the basis of a formal description of the ASN.1 type, characterised by the fact that it includes the following operations:

- identifying (102) the type of record to be decoded, the identification corresponding to at least a first type (GSM) and at least a second type (GPRS) of records to be decoded,

- providing a decoder (10) including an interpreter of the ASN.1 type (18),

- providing (110) said formal description of the ASN.1 type of the records to be decoded,

- self-generate, by means of said interpreter (18) and in relation to the aforementioned description, an updated decoder version of at least a first (114) and at least a second (116) type according to the type of record to be decoded, and

- supplying (118) said files to be decoded (14) to the decoder (114, 116) self-generated in this way, so as to output (120) said decoded records in text format.

2. Method as per claim 1, characterised by the fact that said at least a first type of record and said at least a second type of record is selected from the group consisting of GSM, GPRS or UMTS records.

3. Method as per any one of the previous claims, characterised by the fact that it includes the operation of selecting one of the said at least first (114) and said at least second (116) type of decoder, and of parameterising the decoder selected in relation to at least one parameter selected from the group made up of:

- name of log file to be decoded (104), and

- output format of the decoded file (106).


4. Method as per claim 3, characterised by the fact that said output format of the decoded file is selected from the following:

- 5 - a long format, in which the decoding, the length and the contents in hexadecimal are given for each record field, and
- a short format, for which only the decoding is given for each record field.

5. System for decoding charging data records (CDR) generated
10 in a mobile telephone network operating according to the method as per any one of the previous claims.


1/2

FIG. 1



2/2

FIG. 2



INTERNATIONAL SEARCH REPORT

International Application No

PCT/03/01978

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 H04M15/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04M

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ, INSPEC

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	WO 00 59199 A (CANAVAN ANGELA ROSE ;GAULT WILLIAM JAMES (GB); ANDERSON SAMUEL (GB) 5 October 2000 (2000-10-05) page 6, line 23 -page 9, line 8 page 14, line 8 -page 15, line 9 ---	1-5
Y	US 6 134 307 A (HAKL SHAWN PAUL ET AL) 17 October 2000 (2000-10-17) column 4, line 35 -column 5, line 46 ---	1-5
A	US 2001/040947 A1 (GEISBUSCH FERDINAND ET AL) 15 November 2001 (2001-11-15) page 2, line 15 - line 18 page 3, line 21 - line 24 ---	1-5
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

13 May 2003

Date of mailing of the international search report

03. 06. 2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

CATHARINA KARLSSON/JA

INTERNATIONAL SEARCH REPORT

International Application No

PCT/A 03/01978

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	WO 99 09733 A (TELIA AB) 25 February 1999 (1999-02-25) page 6, line 5 -page 14, line 5 page 28, line 4 -page 30, line 5 -----	1-5

INTERNATIONAL SEARCH REPORT

International Application No

PCT/03/01978

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0059199	A	05-10-2000	AU 3312600 A CA 2363430 A1 EP 1163791 A1 WO 0059199 A1	16-10-2000 05-10-2000 19-12-2001 05-10-2000
US 6134307	A	17-10-2000	NONE	
US 2001040947	A1	15-11-2001	DE 10000825 A1 CN 1311603 A EP 1119174 A2 JP 2001292253 A	19-07-2001 05-09-2001 25-07-2001 19-10-2001
WO 9909733	A	25-02-1999	SE 512479 C2 EE 200000084 A EP 1013067 A1 NO 20000643 A SE 9702937 A WO 9909733 A1	20-03-2000 16-10-2000 28-06-2000 12-04-2000 15-02-1999 25-02-1999